



NOTES:

1. UL/CUL LISTED ABQK.
2. FOR INDOOR & OUTDOOR USE.
3. 20 AWG GALVANIZED, ASTM-A653/A924, POWDER COATED.
4. (1) 1/2" ELECTRICAL KNOCKOUTS.
5. (6) MOUNTING HOLES.
6. 3 YEAR WARRANTY

GENERAL:

1. REFER TO PRODUCT IOM FOR INSTALLATION DETAILS.
2. USE INTERLOCK SWITCHES ON ALL ACCESSES TO LAMPS.
3. CAUTION: NEVER LOOK AT LAMPS WHEN LIT – EYE AND SKIN DAMAGE MAY RESULT FROM EXPOSURE.

Parts List

"A" DIM	QTY	Model #	Part #	Description
		DLX-HO-120-277	57806550	DLX-N Dual Lamp Single Ended High Output NEMA 4X Fixture - 120-277V Lamp Lengths from 12" to 31"
11"		SEL-12-T508-HO-EL	82688129	SEL 12" Single Ended O8 Base High Output EncapsuLamp
15"		SEL-16-T508-HO-EL	82688169	SEL 16" Single Ended O8 Base High Output EncapsuLamp
19"		SEL-20-T508-HO-EL	82688209	SEL 20" Single Ended O8 Base High Output EncapsuLamp
23"		SEL-24-T508-HO-EL	82688249	SEL 24" Single Ended O8 Base High Output EncapsuLamp
30"		SEL-31-T508-HO-EL	82688319	SEL 31" Single Ended O8 Base High Output EncapsuLamp

D	10/4/21	REVISED LAMP VOLTAGE
C	6/11/21	REVISED LAMP OPTIONS
B	5/3/21	REVISED LAMP OPTIONS
A	11/2/20	FIRST ISSUE

Rev	Date	Description
-----	------	-------------

UVR
UV RESOURCES

Description: MULTIPLE SLX FIXTURE
DUCT MOUNTED INSTALLATION

PN: 57506550

Rev:	Date:	Dwg No.	1 of 1
C	11/1/20	98000554	