

PLAN VIEW
TYPICAL SINGLE FIXTURE LAYOUT

APPLICATION NOTES:


1. AT LEAST $40\mu\text{W}/\text{cm}^2$ OF UV ENERGY IN ALL AREAS OF UPPER ROOM UV ZONE IS RECOMMENDED.

QTY OF GLO-150 FIXTURES	ROOM SQ. FT.	QTY OF GLO-225 FIXTURES	ROOM SQ. FT.	QTY OF GLO-310 FIXTURES	ROOM SQ. FT.
1	150	1	225	1	310
2	300	2	450	2	620
3	450	3	675	3	930
		4	900	4	1245
		5	1125	5	1555
		6	1350	6	1865
		7	1575	7	2175

OTHER:

1. REFER TO PRODUCT IOM FOR INSTALLATION DETAILS.
2. FIXTURE BOTTOM MUST BE MOUNTED 7 FEET (84") OR HIGHER.
3. OBSERVE SURROUNDINGS FOR OBSTRUCTIONS IN UPPER ROOM THAT COULD CAUSE REFLECTED UV-C INTO LOWER ROOM.
3. CAUTION: DO NOT OPERATE FIXTURE WITHOUT BAFFLES SECURED.
4. CAUTION: DO NOT LOOK INTO A LIT FIXTURE AT ANY TIME.
5. CAUTION: TURN OFF AND UNPLUG FIXTURE BEFORE SERVICING.
6. CAUTION: WEAR GOGGLES AND A FULL FACE MASK WHEN WORKING AROUND THIS UNIT.
7. CAUTION: DO NOT LET ANY LIGHT STRIKE YOUR EYES WHEN DE-ENERGIZING.

Rev	Date	Description
B	5/15/2020	REVISED APPLICATION NOTE 1
A	5/6/2020	GENERAL REVISIONS
0	8/21/14	FIRST ISSUE

Rev	Date	Description
		
Description: GLO ROOM LAYOUT PLAN VIEW - SINGLE FIXTURE		
PN: n/a		
Rev: B	Date: 7/14/14	Dwg No. 41000103
		1 of 1