



ISOMETRIC VIEW
TYPICAL SMALL ROOM

- APPLICATION NOTES:
1. AT LEAST 40uW/cm² OF UV ENERGY IN ALL AREAS OF UPPER ROOM UV ZONE IS RECOMMENDED.
 2. OBSERVE SURROUNDINGS FOR OBSTRUCTIONS IN UPPER ROOM THAT COULD CAUSE REFLECTED UV-C INTO LOWER ROOM.
 3. CAUTION: DO NOT OPERATE FIXTURE WITHOUT Baffles SECURED.
 4. CAUTION: DO NOT LOOK INTO A LIT FIXTURE AT ANY TIME.
 5. CAUTION: TURN OFF AND UNPLUG FIXTURE BEFORE SERVICING.
 6. CAUTION: WEAR GOGGLES AND A FULL FACE MASK WHEN WORKING AROUND THIS UNIT.
 7. CAUTION: DO NOT LET ANY LIGHT STRIKE YOUR EYES WHEN DE-ENERGIZING.

QTY OF GLO-150 FIXTURES	ROOM SQ. FT.	QTY OF GLO-225 FIXTURES	ROOM SQ. FT.	QTY OF GLO-310 FIXTURES	ROOM SQ. FT.
1	150	1	225	1	310
2	300	2	450	2	620
3	450	3	675	3	930
		4	900	4	1245
		5	1125	5	1555
		6	1350	6	1865
		7	1575	7	2175

OTHER:
1. REFER TO PRODUCT IOM FOR INSTALLATION DETAILS.
2. FIXTURE BOTTOM MUST BE MOUNTED 7 FEET (84") OR HIGHER.

3. OBSERVE SURROUNDINGS FOR OBSTRUCTIONS IN UPPER ROOM THAT COULD CAUSE REFLECTED UV-C INTO LOWER ROOM.
3. CAUTION: DO NOT OPERATE FIXTURE WITHOUT Baffles SECURED.
4. CAUTION: DO NOT LOOK INTO A LIT FIXTURE AT ANY TIME.
5. CAUTION: TURN OFF AND UNPLUG FIXTURE BEFORE SERVICING.
6. CAUTION: WEAR GOGGLES AND A FULL FACE MASK WHEN WORKING AROUND THIS UNIT.
7. CAUTION: DO NOT LET ANY LIGHT STRIKE YOUR EYES WHEN DE-ENERGIZING.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF UV RESOURCES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT WRITTEN PERMISSION IS PROHIBITED

OTHERWISE SPECIFIED. STANDARD TOLERANCE APPLIES

DEPT	APPROVAL	DATE
PROD		
ENGR / QA		

C	05/22/2025	FORMAT UPDATE		HAHN
B	5/15/2020	REVISED APPLICATION NOTE 1		
A	5/6/2020	GENERAL REVISIONS		
0	8/21/14	FIRST ISSUE		
REV	DATE	DESCRIPTION OF CHANGE		DFT
SCALE	NOT DRAWN TO SCALE	PAGE	1 OF 1	



GLO ROOM LAYOUT ISOMETRIC VIEW		REV
DRAWING NO	41000101	C